





VF150FAN AIR FILTRATION UNIT INSTALLATION MANUAL



Responsibility: Cathi Southern Identification Number: 6377

Version: Version Date: 29/04/2020





Table of Contents

1.0	Safety Advice	. 3
	Overview	
	Installation	
	Bill of Materials	
5.0	Dimensions	. 4
6.0	Internal Detail	

Responsibility:Cathi SouthemIdentification Number:6377Version:2Version Date:29/04/2020



1.0 Safety Advice

- Keep out of reach of children
- Refer to Safety Data Sheet
- Ensure adequate ventilation when removing filter from pack and installing.
- Do not puncture the container or otherwise interfere with the product as this will reduce the effectiveness and/or produce harmful vapours.
- First Aid Information: Poison Information Centre in each State capital city can provide additional assistance for:
 - o Scheduled Poisons: Phone (Australia 13 1126)
 - Ingestion: Rinse mouth with water. Do NOT induce vomiting. Seek medical assistance.
 - Eyes & Skin: Be careful to avoid contact with contents, or fumes from the filter as they may cause irritation to eyes, skin or breathing passages. If contact occurs wash affected area with plenty of water.
 - Inhalation: Remove victim from exposure. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered.
 - Seek medical advice if symptoms persist.

2.0 Overview

The air filtration system is designed to treat wastewater odour emissions entering the inlet compartment at the base of the unit. The foul air is treated by McBerns Proprietary Combined Media Cartridges, which is then emitted to atmosphere through the top compartment. The odour control unit is fabricated from uPVC material with the exterior coated in 'Pale Eucalypt'.

Responsibility:Cathi SouthernIdentification Number:6377Version:2Version Date:29/04/2020



3.0 Installation


Note: Failure to comply with installation procedure will result in a void of warranty.


- 1. Ensure on delivery of filter all components are provided
- 2. Slide the filter housing over the vent port
- 3. Remove cap of housing by twisting off
- 4. Remove cartridge from packaging and insert "THIS WAY UP ↑" into housing of filter
- 5. Screw cap back on
- 6. We recommend that filter housing is secured to vent pipe with s/s screws or adhesive
- 7. Adaptions can be purchased from McBerns if required.

4.0 Bill of Materials

Item	Item No.	Description	Qty.
1	F150HOUSING VF150 Housing Assembly		
2	DOMENUTM8 Dome Nut M8 Stainless Steel		
3	F150MC 150mm Media Cartridge		1
4	FH100FANGRN 100mm Hurricane S2 Top (Pale Eucalypt)		1

5.0 Dimensions






Responsibility:	Cathi Southern	Identification Number:	6377
Version:	2	Version Date:	29/04/2020



6.0 Internal Detail



Responsibility:Cathi SouthernIdentification Number:6377Version:2Version Date:29/04/2020