

MCBERNS

INNOVATIVE SOLUTIONS

GM FILTER RANGE

Why choose a Ground Mount Filter?

- A preferred replacement for old corroded vent poles
- Easy installation and safe servicing at ground level
- Suitability for commercial scale odour problems
- Will last many years exposed to the harsh elements
- Fully rechargeable with our specially formulated
- McBerns combined media cartridges
- Robust, vandal proof and compact construction



McBerns GM Filters

Ground Mount Odour Filters improve on site safety, maintenance and expenditure as all servicing is carried out at ground level - there is no longer a need to work from heights, cranes or cherry pickers.

The Ground Mount Filters use our combined media filtration method incorporating our specially formulated media cartridges, activated carbon and natural minerals to adsorb, absorb and treat the noxious gases in sewerage networks.

They are suitable for commercial scale odour problems. They are robust vandal proof and will last many years exposed to the harsh environment.

Increasingly the ground mounted filters are being used to replace old corroded vent poles, saving on all future maintenance costs.





GM 700 ODOUR FILTER

Part Number:	GM700
Description:	Flow rates from 60L / sec
Application:	Sewage Pump Stations, Receiving Manholes, Air Valves
Material / Finish:	PVC Painted Pale Eucalypt
Weight:	105kg
Media Replacement:	4 X F375MC
Options:	Extraction, Ventpole
Dimensions:	609W x 880D x 821H



GM 450 ODOUR FILTER

Part Number:	GM450
Description:	Flow rates from 45L / sec
Application:	Sewage Pump Stations, Receiving Manholes, Air Valves
Material / Finish:	PVC Painted Pale Eucalypt
Weight:	95kg
Media Replacement:	3 X F375MC
Options:	Extraction, Ventpole
Dimensions:	609W x 880D x 821H



GM 375 ODOUR FILTER

Part Number:	GM375
Description:	Flow rates from 30L / sec
Application:	Sewage Pump Stations, Receiving Manholes, Air Valves
Material / Finish:	PVC Painted Pale Eucalypt
Weight:	58kg
Media Replacement:	2 X F375MC
Dimensions:	658W x 470D x 540H



GM 375 TOP MOUNT ODOUR FILTER

Part Number:	GM375T
Description:	Flow rates from 30L / sec
Application:	Sewage Pump Stations, Receiving Manholes, Air Valves
Material / Finish:	PVC Painted Pale Eucalypt
Media Replacement:	2 X F375MC
Options:	Extraction, Ventpole
Dimensions:	470W x 609D x 813H



GM 300 ODOUR FILTER

Part Number:	GM300
Description:	Flow rates from 15L / sec
Application:	Sewage Pump Stations, Receiving Manholes
Material / Finish:	PVC Painted Pale Eucalypt
Weight:	23kg
Media Replacement:	1 X F300MC
Dimensions:	40W x 470D x 460H



GM 300 No Cover Odour Filter

Part Number:	GM300NC
Description:	Flow rates from 15L / sec
Application:	Sewage Pump Stations, Receiving Manholes
Material / Finish:	PVC Painted Pale Eucalypt
Weight:	23kg
Media Replacement:	1 X F300MC
Dimensions:	415W x 405D x 460H



GM 150 Odour Filter

Part Number:	GM150
Description:	Flow rates from 5L / sec
Application:	Sewage Pump Stations, Receiving Manholes
Material / Finish:	PVC Painted Pale Eucalypt
Weight:	5kg
Media Replacement:	1 X F150MC
Dimensions:	315W x 470D x 256H



MCBERNS

INNOVATIVE SOLUTIONS

ODOUR MANAGEMENT
SAFETY ACCESS COVERS
DESIGN & FABRICATION
DATA ANALYTICS

MCBERNS PTY LTD
ABN: 56 060 984 107
Address: 11 Tectonic Crescent,
Kunda Park, Qld, 4556
Phone: +61 7 5445 1646
Fax: +61 7 5445 1743
Email: mail@mcberns.com

Noel Southern: 0411 745 458
Paul O'Kane: 0459 396 157
Stuart Darby: 0413 436 683

www.mcberns.com